



## BCI® 3301 Hand-Held Pulse Oximeter

- Durable yet lightweight design.
- Ergonomically designed to fit your hand comfortably.
- Bright, easy-to-read LED numerals.
- Quantitative pulse strength bar on screen.
- Fast, reliable SpO<sub>2</sub> and pulse rate measurements.
- Stores data for up to 99 different patients.
- Simple On/Off control with auto shutoff to conserve battery life.
- Powered by 3 easily replaceable "C" batteries.
- Monitor patients ranging from neonate to adult.
- Genuine BCI® reusable and disposable sensors available.

### Technical Specifications

#### DISPLAYS, INDICATORS AND KEYS

- **SpO<sub>2</sub>**  
LED numeric display 0.46 inches (11.68 mm) high
- **Pulse Rate**  
LED numeric display 0.38 inches (9.65 mm) high
- **Pulse Strength**  
Logarithmically scaled, 8-segment bar graph
- **Keys**  
ON and OFF Keys

#### SPO<sub>2</sub>

- **Range**  
0 to 99% SpO<sub>2</sub> (functional)
- **Accuracy**  
±2% at 70 to 99%; <70% unspecified
- **Averaging**  
8 beat average

#### PULSE RATE

- **Range**  
30-254 bpm
- **Accuracy**  
±2% or 2 bpm (whichever is greater) at 30-254 bpm
- **Averaging**  
8 second average

#### MEMORY

1,000 Spot Checks, up to 99 patients

#### POWER REQUIREMENTS

(3) "C" alkaline or NiCAD batteries

#### BATTERY LIFE

Approximately 24 hours in Continuous Use Mode  
1500 spot checks, 1 min ON, 2 min OFF

#### AUXILIARY PRINTER OUTPUT

RS232C

#### DIMENSIONS

6.8" H x 3.3" W x 1.5" D  
(17.2 cm H x 8.4 cm W x 3.7 cm D)

#### WEIGHT

16.5 oz. (462 grams) with batteries

#### ENVIRONMENTAL

- **Operating Temperature**  
32°F to 131°F (0°C to 55°C)
- **Storage Temperature**  
-29°F to 158°F (-34°C to 70°C)
- **Relative Humidity**  
10-95% (storage)  
15-95% (operating)

#### MECHANICAL DURABILITY TEST RESULTS

- **Vibration Testing**  
In compliance with MIL-STD-810E, Method 514.4 IEC 68-2-6, IEC 68-2-34
- **Shock Testing**  
In compliance with IEC 68-2-27
- **Drop Testing**  
Exceeded UL 544 testing recommendations

#### STANDARDS

EN60601-1 (IEC 601-1)  
CAN/CSA 601.1, CAN/CSA NRTL/C

#### REGULATORY COMPLIANCE

ISO 9001/ISO 13485

#### CATALOG NUMBER

- **3301**  
Hand-Held Pulse Oximeter

Information subject to change without notice. Please read the Instructions for Use supplied with the product for detailed instructions, warnings and cautions.

Q-Line for U.S.A. customers: call 1-800-348-1842 for clinical application information.

For more information, please call Smiths Medical PM, Inc., at 262-542-3100 or 800-558-2345, or your Smiths Medical distributor.

#### Smiths Medical PM, Inc.

Patient Monitoring and Ventilation

N7W22025 Johnson Drive, Waukesha, Wisconsin 53186 USA

Phone: 262-542-3100 Fax: 262-542-0718 Toll-Free: 800-558-2345

[www.smiths-medical.com/bci](http://www.smiths-medical.com/bci)

Smiths Medical, part of the global technology business Smiths Group

BCI and the Smiths Medical design mark are trademarks of the Smiths Medical family of companies.

The symbol © indicates the trademark is registered in the U.S. Patent and Trademark Office and certain other countries.

All other names and marks mentioned are the trade names, trademarks or service marks of their respective owners.

©2008 Smiths Medical family of companies. All rights reserved. BCI 3301 Rev.12 05/08

**Mountainside Medical Equipment**

Phone: 1-888-687-4334

[www.mountainside-medical.com](http://www.mountainside-medical.com)

**smiths medical**